



VCA Headquarters
1 The Eastgate Office Centre
Eastgate Road
Bristol, BS5 6XX
United Kingdom

Switchboard: +44 (0) 117 951 5151
Main Fax: +44 (0) 117 952 4103
Email: enquiries@vca.gov.uk
Web: www.vca.gov.uk

THE UNITED KINGDOM VEHICLE APPROVAL AUTHORITY

COMMUNICATION CONCERNING THE ~~TYPE-APPROVAL~~⁽¹⁾, ~~EXTENSION OF TYPE-APPROVAL~~⁽¹⁾, ~~REFUSAL OF TYPE-APPROVAL~~⁽¹⁾, ~~WITHDRAWAL OF TYPE-APPROVAL~~⁽¹⁾ OF A TYPE OF ~~VEHICLE/COMPONENT/SEPARATE TECHNICAL UNIT~~⁽¹⁾ WITH REGARD TO DIRECTIVE 95/28/EEC, AS LAST AMENDED. RELATING TO THE BURNING BEHAVIOUR OF MATERIALS USED IN THE INTERIOR CONSTRUCTION OF CERTAIN CATEGORIES OF MOTOR VEHICLES.

Type Approval No: e11*95/28*0002*02

Reason for Extension: To cover:

- 1) Change to manufacturers name and address
- 2) Addition of application in luggage racks

SECTION I

0.1. Make (trade name of manufacturer): Holdsworth Fabrics Ltd

0.2. Type and commercial description(s):
Vigor

All cut pile, face to face woven jacquard upholstery Moquette

Unbacked

Composition:

53% Wool

11% Nylon

36% Cotton

Weight: 820 g/sq m +/-5%

Backed

Composition:

49% Wool

10% Nylon

33% Cotton

8% Latex backcoating

Weight: 890 g/sq m +/-5%

0.3. Means of identification of type if marked on the ~~vehicle/component/separate technical unit~~ ⁽¹⁾
⁽²⁾:Not applicable

0.3.1. Location of that marking: Not applicable

0.4. Category of vehicle ⁽³⁾:Not applicable

0.5. Name and address of manufacturer:

Holdsworth Fabrics Ltd
Meltham Mills
Meltham
West Yorkshire
HD9 4AY

0.7. In the case of components and separate technical units, location and method of affixing of the EEC approval mark: Label attached to piece part

0.8. Address(es) of assembly plant(s): Not applicable

SECTION II

1. Additional information (where applicable): See Addendum
2. Technical service responsible for carrying out the tests: Vehicle Certification Agency
3. Date of test report: As before (20 December 2006)
4. Number of test report: As before (ESF069898c)
5. Remarks (if any): See Addendum
6. Place: BRISTOL
7. Date: 28 SEPTEMBER 2010

8. Signature: 

A. W. STENNING
Head of Technical and Quality Group

9. The index to the information package lodged with the approval authority, which may be obtained on request, is attached.

(¹) Delete where not applicable.

(²) If the means of identification of type contains characters not relevant to the description of the vehicle, component or separate technical unit types covered by this type-approval certificate such characters shall be represented in the documentation by the symbol: '?' (e.g.: ABC?? 123

ADDENDUM

to EEC Type Approval Certificate No: e11*95/28*0002*02

concerning the type approval of a vehicle with
regard to Directive 95/28/EC

1. Additional information

1.1. Material is suitable for installation

- as roof lining ⁽¹⁾
- as rear or side wall lining ⁽¹⁾
- as seat upholstery ⁽¹⁾ or covering ⁽¹⁾
- as luggage rack ⁽¹⁾
- for other purpose(s) (please specify):Not applicable

Components as complete devices (seats, separation walls, luggage racks, etc. ⁽¹⁾) are suitable for installation in M₂/M₃ vehicles ⁽¹⁾.

1.2. Compliance with the burning rate requirements has been checked in

the horizontal ↔

Vertical ↔

Compliance with the melting rate has been checked for components according Annex V, symbol ^(v):No

Compliance has been checked for components approved as complete devices, symbol ^(cb):No

1.3. Any restrictions of use and installation requirements:

5. Remarks:None

⁽¹⁾ Delete where not applicable.



VCA Headquarters
1 The Eastgate Office Centre
Eastgate Road
Bristol, BS5 6XX
United Kingdom

Switchboard: +44 (0) 117 951 5151
Main Fax: +44 (0) 117 952 4103
Email: enquiries@vca.gov.uk
Web: www.vca.gov.uk

APPROVAL NUMBER: e11*95/28*0002*02

INFORMATION PACKAGE CONTENTS

INDEX

REVISION NUMBER: 02 (Two)

Total number of sheets:	5 (Five)
Number of separate drawings:	0 (Nil)
Number of separate photographs:	0 (Nil)

Reasons for Revision: See approval certificate

Revision date
&
Office stamp



Holdsworth Fabrics Ltd Information Document for Vigor

Relating to EEC component type-approval of interior materials for certain categories of motor vehicles with respect to their burning behaviour (Directive 95/28/EEC, as last amended by directive .../.../EEC).

0. General

0.1 Make (trade name of manufacturer):

Holdsworth Fabrics Ltd

0.2 Type and general commercial description(s):

Vigor

All cut pile, face to face woven jacquard upholstery velvet

Unbacked

Composition:

53% Wool

11% Nylon

36% Cotton

Weight: 820 g/sq m +/-5%

Backed

Composition:

49% Wool

10% Nylon

33% Cotton

8% Latex backcoating

Weight: 890 g/sq m +/-5%

0.5 Name and address of manufacturer:

Holdsworth Fabrics Ltd
Meltham Mills
Meltham
West Yorkshire
HD9 4AY

0.7 In the case of components and separate technical units, location and method of affixing of the EEC approval mark:

Label attached to piece, example in file [label for annex IV and V](#).



0.8 Address(es) of assembly plant(s):

1. Interior materials

1.1 Material(s) used for the interior lining of the roof

1.1.1 Base material(s)/designation:

Vigor

All cut pile, face to face woven jacquard upholstery velvet

1.1.2 Composite/single material, number of layers:

Unbacked: Single material, single layer

Backed: Single material, single layer

1.1.3 Type of coating:

Unbacked: None

Backed: Non flame retardant acrylic polymer

1.1.4 Minimum/maximum thickness:

Unbacked: Min = 3.8 mm/ Max = 4.8 mm

Backed: Min = 3.8 mm/ Max = 4.8 mm

1.1.5 Type approval number, if available:

1.2 Material(s) used for the rear and side walls.

1.2.1 Base material(s)/designation:

Vigor

All cut pile, face to face woven jacquard upholstery velvet



1.2.2 Composite/single material, number of layers:

Unbacked: Single material, single layer

Backed: Single material, single layer

1.2.3 Type of coating:

Unbacked: None

Backed: Non flame retardant acrylic polymer

1.2.4 Minimum/maximum thickness:

Unbacked: Min = 3.8 mm/ Max = 4.8 mm

Backed: Min = 3.8 mm/ Max = 4.8 mm

1.2.5 Type approval number, if available:

1.3 Material(s) used for the floor

N/A

1.4 Material(s) used for the upholstery of the seats.

1.4.1 Base material(s)/designation:

Vigor

All cut pile, face to face woven jacquard upholstery velvet

1.4.2 Composite/single material, number of layers:

Unbacked: Single material, single layer

Backed: Single material, single layer

1.4.3 Type of coating:



Unbacked: None

Backed: Non flame retardant acrylic polymer

1.4.4 Minimum/maximum thickness:

Unbacked: Min = 3.8 mm/ Max = 4.8 mm

Backed: Min = 3.8 mm/ Max = 4.8 mm

1.4.5 Type approval number, if available:

1.5 Material(s) used for heating and ventilation pipes.

N/A

1.6 Material(s) used for luggage racks.

1.6.1 Base material(s)/designation:

Vigor

All cut pile, face to face woven jacquard upholstery velvet

1.6.2 Composite/single material, number of layers:

Unbacked: Single material, single layer

Backed: Single material, single layer

1.6.3 Type of coating:

Unbacked: None

Backed: Non flame retardant acrylic polymer

1.6.4 Minimum/maximum thickness:

Unbacked: Min = 3.8 mm/ Max = 4.8 mm

Backed: Min = 3.8 mm/ Max = 4.8 mm

1.6.5 Type approval number, if available:



1.7 Material(s) used for other purposes.

N/A

